## **Elbow Grease Enterprises, LLC Safety Audit Form**

Project:	Auditor:			Date:
	Inspection Item	Yes	<u>No</u>	<u>Notes</u>
STAIRS AND STAIRWAYS				
Do standard stair rails or handrails on all stairways have at least four risers?				
Are all stairways at least 22 inches (55.88 centimeters) wide?				
inches (76.20 cer extend 22 inches 12 feet (3.6576 n	nding platforms not less than 30 ntimeters) in the direction of travel and (55.88 centimeters) in width at every neters) or less of vertical rise?			
Do stairs angle no more than 50 and no less than 30 degrees?				
Are stairs of hollow-pan type treads and landings filled to the top edge of the pan with solid material?				
Are step risers on stairs uniform from top to bottom?				
Are steps slip-resistant?				
Are stairway handrails located between 30 inches (76.20 centimeters) and 34 inches (86.36 centimeters) above the leading edge of stair treads?				
Do stairway handrails have at least 3 inches (7.62 centimeters) of clearance between the handrails and the wall or surface they are mounted on?				
Where doors or gates open directly on a stairway, is a platform provided so the swing of the door does not reduce the width of the platform to less than 21 inches (53.34 centimeters)?				
Are stairway handrails capable of withstanding a load of 200 pounds (90.7 kilograms), applied within 2 inches (5.08 centimeters) of the top edge in any downward or outward direction?				
Where stairs or stairways exit directly into any area where vehicles may be operated, are adequate barriers and warnings provided to prevent employees from stepping into the path of traffic?				
Do stairway landings have a dimension measured in the direction of travel at least equal to the width of the stairway?				
Is the vertical distance between stairway landings				