## **Elbow Grease Enterprises, LLC Safety Audit Form**

Project: Auditor:			Date:
<u>Inspection Item</u>	Yes	<u>No</u>	<u>Notes</u>
EXITING OR EGRESS - EVACUATION			
Are all exits marked with an exit sign and illuminated by a reliable light source?			
Are the directions to exits, when not immediately			
apparent, marked with visible signs?			
Are doors, passageways or stairways that are neither			
exits nor access to exits, but could be mistaken for exits, appropriately marked "NOT AN EXIT", "TO BASEMENT", "STOREROOM", etc.?			
Are exit signs labeled with the word "EXIT" in lettering			
at least 5 inches (12.70 centimeters) high and the			
stroke of the lettering at least I/2- inch (1.2700			
centimeters) wide?			
Are exit doors side-hinged?			
Are all exits kept free of obstructions?			
Are at least two means of egress provided from			
elevated platforms, pits, or rooms where the absence			
of a second exit would increase the risk of injury from			
hot, poisonous, corrosive, suffocating, flammable, or			
explosive substances?			
Are there sufficient exits to permit prompt escape in case of emergency?			
Are special precautions taken to protect employees			
during construction and repair operations?			
Is the number of exits from each floor of a building and			
the number of exits from the building itself appropriate			
for the building occupancy load?			
Are exit stairways that are required to be separated			
from other parts of a building enclosed by at least 2-			
hour fire-resistive construction in buildings more than			
four stories in height, and not less than 1-hour fire-			
resistive construction elsewhere?			
Where ramps are used as part of required exiting from			
a building, is the ramp slope limited to 1 foot (0.3048			
meter) vertical and 12 feet (3.6576 meters) horizontal?			
Where exiting will be through frameless glass doors,			
glass exit doors, storm doors, etc., are the doors fully			
tempered and meet the safety requirements for human impact?			